

OIL CIRCULATION TEMPERATURE CONTROL UNIT

170℃、200℃、250℃、300℃、350℃



SPECIFICATIONS :

Item	Model	TOS-1020	TOS-1020 T	TOS-2020	TOS-1025	TOS-3020	TOS-4020	TOS-1530	TOS-4030
		TOV-1020	TOV-1020T	TOV-2020	TOV-1025	TOV-3020	HTOV-4020	TOV-1530	TOV-4030
Control range	℃	60 ~ 200		60 ~ 250		60 ~ 200		60 ~ 300	
Accuracy	℃	±1 or ±0.1							
Control range	PID	Proportional integral derivative							
Power	ORDER	3 φ 220 / 380V / 60HZ or other							
Medium	OIL	OIL							
Method	OIL / Water	Indirect							
Heating	KW	9	9 x 2	9	10	10 x 2	10 x 2	10	10 x 2
Pump	HP	1	1 x 2	2	1	3	4	1.5	4
Pressure	Kg / cm ²	4.5	4.5 x 2	6	4.5	4.5	10	6.5	13
Pump flow	L / min	70	70 x 2	90	70	115	100	65	100
Tank	Liter	10	16	10	10	30	30	16	30
Power supply	KW	9.75	9.75 x 2	10.5	10.75	22.25	23	11.2	23
Cooling pipe	Inch	1/2"							
Circulation	Inch	3/8"-4 x 4 or 3/4"-1 x 1		3/4"-2 x 2 or 1" -1 x 1		3/4"-2 x 2 or 1"-1 x 1		3/8"-4 x 4 or 3/4"-1 x 1	
Dimension	L x W x H (cm)	70 x 35 x 70	70 x 40 x 70	70 x 35 x 70		70 x 35 x 70		100 x 65 x 110	70 x 40 x 75
Approx. weight	KG	70	120	75	75	120 ~ 130		80	130

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE ◦
 SPECIAL POWER AND DESIGN UPON REQUEST ◦
 SPECIAL DESIGN UPON REQUEST ◦