

DEHUMIDIFIED DRIER HLDD-30~HLDD-1200

ITEM	MODE	HLDD-30	HLDD-60	HLDD-100	HLDD-150	HLDD-200
TEMP. RANGE	°C	40 ~ 180				
DRYING CAPACITY	M ³ /HR	30	60	100	150	200
DRYING BLOWER	KW	0.2	0.5	0.85	1.1	1.9
REGENERATIVE BLOWER	KW	0.2	0.2	0.5	0.5	0.5
REGENERATIVE HEATER	KW	2.5	3.5	4.5	5.5	6.5
DRYING OUTLET	INCH	1.5	2	2	2	2.5
DRYING INLET	INCH	1.5	2	2	2	2.5
REGENERATIVE PIPING	INCH	1	1-1/2	1-1/2	1-1/2	2
COOLING WATER CAPACITY	LITER	8	10	12	15	20
COOLING WATER PIPING	INCH	3/8	3/8	1/2	1/2	1/2
COOLING WATER PRESSURE	KG / CM ²	1-2				
TOTAL LOAD OF POWER	KW	2.8	4.2	5.9	7.1	8.9
DIMENSION	WxDxH (CM)	40 X 50 X 100	50 X 65 X 120	55 X 70 X 135	60 X 80 X 150	60 X 80 X 150
WEIGHT	KG	150	160	170	230	250

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE ◦

SPECIAL POWER AND DESIGN UPON REQUEST ◦

SPECIAL DESIGN UPON REQUEST ◦