

3D PRINTER

P-110A ~ P-110B

P-110ASV ~ P-110BSV

Item	Mode	P-110 A	P-110 B	P-110 ASV	P-110 BSV
Handle temperature	°C	5 ~ 35			
Humidity	%	25 ~ 90			
Nozzle size	mm	0.4			
Power	Input power	110V~240V AC2~5A 50~60Hz			
	Output power	90 W			
Material diameter	mm	1.75			
Material	-----	PLA			
Printer speed	Mm / S	20 ~ 70	20 ~ 70	20 ~ 70	20 ~ 70
Printer temperature	°C	190 ~ 220	190 ~ 220	190 ~ 220	190 ~ 220
Load temperature	°C	Room temperature			
Thickness of printer	mm	0.1 ~ 0.4			
Product dimensions	mm	110 x 110 x 110			
File Format	-----	STL / OBJ / GCODE or beyond			
Operating System	-----	Windows XP Mac OSX 10.6.8 or beyond			
Countries	Joint	SD	SD	SD	SD
	Link	USB	USB	USB	USB
Dimension	L x W x H (mm)	195x210x275	195x210x275	195x210x275(300)	195x210x275(300)
Net weight	KG	2.4	2.4	2.7	2.7
Gross weight	KG	4	4	4	4

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE ◦

SPECIAL POWER AND DESIGN UPON REQUEST ◦

SPECIAL DESIGN UPON REQUEST ◦

